

# Straßmayr



An additional third axle drive and control of the front wheel allow easy and independent movement of the set on the construction site.



The spraying bar, suitable for spraying sealing compound or asphalt, allows spraying the edges of a freshly applied layer of bitumen. Mounting on a steel mount enables manual adjustment of the height and inclination angle.

## Cracksealing machine STRASSMAYR RWK 600/500

*The device is designed for preparation and dosing of special sealing compounds and joint fillers heated to a temperature of 180° C.*

The cracksealing machine is built on a two-axle trailer used to prepare a special sealing compound for cracks. The cracksealing machine is equipped with a thermal oil-heated boiler and an efficient hydraulically driven feeding pump. The spray lance with a feeding hose ensures trouble-free crack sealing.

### Technical data:

#### Chassis - two-axle trailer:

- carrying capacity 2,500 kg
- two-axle trailer with overrunning brake
- parking hand-brake
- lighting installation

#### Oil heater system:

- automatic oil heater with a burner
- protection of the heated material against spot overheating

#### Joint sealing installation:

- complete with pump, sealing lance, 4 m hose

Diesel tank: 60 l

Lighting of the work space: headlights

#### Edge sprinkling installation:

- 3 spraying nozzles with a spraying width of 120 mm.
- spraying bar with circulation installation
- allows for turning on nozzles individually
- mechanical adjustment of inclination angle of the spraying bar
- manual adjustment of pressure in the spraying bar



The utilized solution enables a short preparation time of the bitumen for repair work.

#### Boiler:

- effective quantity of the prepared material: approximately 500 l
- thermal oil heated heater
- horizontal mixer, hydraulic drive of the mixer
- Kubota Diesel engine with a hydraulic pump